

# LTE Antenna Optimum 450

**ENQT**  
EXPERTS IN NETWORK  
QUALITY TESTING

TECHNICAL DATA SHEET



Do you have questions about  
our products?



+49 40 35 73 20 65



vertrieb@enqt.de

## Description:

The **LTE Antenna Optimum 450** is specifically designed for 450 MHz LTE networks such as the nationwide 450 MHz network for energy suppliers and critical infrastructures in Germany. It is ideal for use on 450 MHz terminal devices such as smart meter gateways (SMGW) in iMSys as well as for substations and transformer stations. The flat design allows universal installation.

LTE Antenna Optimum 450 is **extremely durable and robust**. It is flame-retardant in accordance with UL 94 V-0, protected against water jets and dust in accordance with IP66 and UV-stable for at least 10 years. This makes the antenna ideal for both indoor and outdoor installations. The antenna is designed for a service life of up to 20 years.

The antenna can be mounted using screws (2-hole mounting), adhesive pads or optional magnets. It can be mounted on metal, wood and plastic surfaces.

## Technical details:

<b>Frequency range</b>	450 - 480 MHz
<b>supported LTE bands</b>	32, 72
<b>Antenna gain max.</b>	2 dBi (≈ 0 dBd)
<b>Antenna gain min.</b>	0 dBi (≈ -2 dBd)
<b>Standing wave ratio* (VSWR)</b>	< 2.5:1
<b>Impedance</b>	50 Ω
<b>Efficiency</b>	> 40 %
<b>Polarization</b>	vertical (if mounted vertically) horizontal (if mounted horizontally)
<b>Antenna type</b>	Wallmount patch
<b>Radiation pattern</b>	omnidirectional (in free space)
<b>Power (max.)</b>	5 W
<b>Cable</b>	low-loss (AA100 type, attenuation < 0.85 dB/m at 2 GHz)
<b>Connector</b>	FAKRA D
<b>Temperature range</b>	-40 °C to +85 °C
<b>Humidity</b>	max. 95 % RH (non-condensing)
<b>Wind resistance</b>	> 150 km/h
<b>IP class</b>	IP66
<b>Flammability</b>	flame-retardant in accordance with UL 94 V-0

<b>UV resistance</b>	min. 10 years
<b>Product lifetime</b>	min. 20 years
<b>Conformity</b>	ROHS, CE
<b>Color</b>	grey